


ST5502 55" Digital Signage Display




Launcher
Quick set-up, access to tools and settings from the Android launcher



Anti-Glare Technology
Optimised for indoor and semi-outdoor use with matte finish and anti-glare technology




Stylish Design
Engineered to offer an expansive canvas to showcase designs



Brighter screen
Display vivid images with up to 450 nits



OPS Slot
Offering a flexible solution to displaying content



InstaShare
Wirelessly display content from your device



Zoom
Compatible with Zoom as well as other leading conferencing solutions



12W x 2 internal speaker

Additional features




Powered by X-Sign
BenQ technology offers a solution for distributing content across your digital signage network. The X-Sign software suite developed in-house allows users to design, deploy and monitor digital content in real time.



Hassle free management
The BenQ exclusive Device Management Solution allows users to manage and monitor digital signage displays across your network. Using DMS Cloud, install and manage android apps on multiple devices with remote access.

Connectivity



- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12

- 1 HDMI Output
- 2 SPDIF
- 3 HDMI 1 (ARC)
- 4 HDMI 2
- 5 DisplayPort
- 6 RS232
- 7 VGA
- 8 PC Line Input
- 9 USB 3.0
- 10 USB 1 & 2
- 11 Audio Output
- 12 LAN

ST5502 55" Specification



| | | | | |
|---|-----------------------|----------------------------|--------------------------------|---------|
| | Model | | ST5502 | |
| Panel | Screen Size | | 55" | |
| | Resolution | | 3840 x 2160 | |
| | Brightness (Typ.) | | 450 | |
| | Contrast Ratio (Typ.) | | 4500:1 | |
| | Viewing Angle (H/V) | | 178 / 178 | |
| | Response Time (G-t-G) | | 8ms | |
| | Backlight Life (hrs) | | 30000 | |
| | Operating Hour | | 18/7 | |
| | Orientation | | Landscape / Portrait | |
| Power | Power Type | | Internal | |
| | Power Supply | | 100V~240V, 50Hz / 60Hz | |
| | Power Consumption | Maximum | | 300 W/h |
| | | Typical | | 280 W/h |
| Standby | | | <0.5W | |
| | Off Mode | | <0.5W | |
| | Wake up | | HDMI / VGA | |
| Environment | Operation Temperature | | 0°C ~ 40°C | |
| | Operating Humidity | | 20% ~ 90% RH non-condensing | |
| Connectivity | Input | VGA | x 1 | |
| | | HDMI | 2.0 x 2 | |
| | | Audio Input | x 1 (3.5mm) | |
| | | Display Port | DP 1.2 x 1 | |
| | Output | HDMI | x 1 (2.0) | |
| | | Audio Output | x 1 (3.5mm) | |
| USB | | USB 3.0 x 1 USB 2.0 x 2 | | |
| RS232 | | x 1 | | |
| RJ45 | | x 1 | | |
| Remote Controller | | x 1 | | |
| Audio | Internal Speaker | | 12W x 2 | |
| Mechanical | Dimension (mm) | Screen | 1233.6 x 708.4 x 76.6 | |
| | | Package | 1364 x 154 x 824 | |
| | Weight (kg) | Screen | 18.4 | |
| | | Package | 25.7 | |
| | Bezel Width (mm) | | 10.7 (Top/Side), 14.9 (Bottom) | |
| Wall Mounting (VESA) (Screw Type /Max. Length) | | 400x200mm M6 x 12mm | | |
| OPS | | Yes | | |



3 year Warranty
Onsite warranty with
optional extension



Demo Fleet
Trial the BenQ Product
portfolio without obligation